


PART # OPA-00A

SPECIFICATIONS:

GEAR REDUCTION: 32:1
 SPEED: 500-1400 RPM
 FLOW RATE MAX.: 0.1 mL PER STROKE EACH OUTLET
 (MAX UPTO 1.0 L PER HOUR @1400 RPM)
 (MIN 150 mL PER HOUR @ 1400 RPM)
 PRESSURE MAX.: 44 PSI, 3 BAR
 SUCTION HEIGHT: 10"
 LUBRICANT: OIL
 VISCOSITY: 20-800 ISO VG
 NO. OF OUTLETS: 4
 ROTATION: USER CONFIGURED BI-DIRECTIONAL
 SEALING: WITH RUBBER SHAFT SEAL
 RUST PROTECTION: SURFACE RUST PROTECTION



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FRUITLAND MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FRUITLAND MFG. IS PROHIBITED.

NAME	DATE	 FRUITLAND 324 Leaside Avenue Stoney Creek, Ontario, CANADA L8E 2N7 Phone: (905) 662-6552 Fax: (905) 662 9875	
CREATED	K.A. 1/10/24		
CHECKED		TITLE:	
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL OR .X = ±.015 .XX = ±.010 .XXX = ±.005		FRUITLAND OIL PUMP SPECS.	
MATERIAL	--	DWG. NO.	REV
		OPA-00A	0
		SCALE: 2:3	WEIGHT:--