

324 Leaside Avenue Stoney Creek, ON Canada L8E 2N7 Tel: 905-662-6552 / TF: 1-800-663-9003 Fax: 905-662-5412

www.fruitlandmanufacturing.com

OILS APPROVED FOR USE IN FRUITLAND VACUUM PUMPS

OIL TYPE	WINTER WEIGHT	SUMMER WEIGHT
FRUITLAND® GREEN™ OIL (100% Biodegradable)	SAME	SAME
¹ SHELL TURBO T OIL	32	68 or 100
¹ ISO COMPRESSOR OIL	100	150
MONOLEC COMPRESSOR OIL*	SAME	SAME
MOBIL SHC 525 (Synthesized Hydrocarbon)	SAME	SAME
¹ MOBIL DTE	LIGHT OR MEDIUM	HEAVY MEDIUM
ANDEROL 497	SAME	SAME
¹ CHEVRON GST	32	68
¹ PENNZOIL PENNZBELL TO OIL	32 or 46	68
¹ TEXACO REGAL R & O OIL	32	68
¹ SAE NON DETERGENT OIL	10 or 20	30 or 40
SHELL ROTELLA 15W-40 MOTOR OIL	SAME	SAME

These oils have been approved for use in Fruitland Vacuum Pumps. Use of these oils will maintain the vacuum pump warranty as well as extend the life of the vacuum pump and ensure proper performance and lubrication.

When operated properly, Fruitland vacuum pumps will run cooler, use less oil and provide much longer service than any other rotary vane vacuum pump.

*Monolec Compressor Oil is colored red and should not be confused with transmission fluid.

¹ Recommended for the best performance and lubrication at all temperature levels.

OILS OR FLUIDS THAT ARE NOT APPROVED FOR USE IN FRUITLAND VACUUM PUMPS

BRAKE FLUID	HYDRAULIC FLUID	TRANSMISSION FLUID
DEF FLUID	POWER STEERING FLUID	USED OIL
GEAR OIL	SCENTED OIL	VEGETABLE OIL
SYNTHETIC OIL		

For more information, please call Fruitland Manufacturing or your local Fruitland Dealer.